

VIDIX CONTROL

Access Control for Every Facility



AXX-PS-3A

CONTROLLER POWER SUPPLY

STANDARD FEATURES

- These units have a wide range of applications for access control, security and CCTV system accessories that require additional power.
- The FACP Interface enables Emergency Egress, Alarm Monitoring, or may be used to trigger other auxiliary devices.

Technical Specifications

AXX-PS-3A

INPUT	6VDC or 12VDC
OUTPUT	6VDC, 12VDC or 24VDC selectable output; 2.5 amp continuous supply current; filtered and electronically regulated outputs; short circuit and thermal overload protection
BATTERY BACKUP	built-in charger for sealed lead acid or gel type batteries; maximum charge current 0.3 amp; battery short circuit protection (circuit breaker)
VISUAL INDICATORS	AC input and DC output LED indicators
OPERATING TEMPERATURE	0° C to 49° ambient
BTU/HR	6VDC: 7.68 BTU/Hr; 12VDC: 15.35 BTU/Hr; 24VDC: 30.71 BTU/Hr
SYSTEM AC INPUT VA REQUIREMENT	6VDC/12VDC: 55.2VA; -24VDC: 115VA
PRODUCT WEIGHT	2.8 Lbs (1.27 kg)
SHIPPING WEIGHT	3.8 Lbs (1.72 kg)
ENCLOSURE	8.5" x 7.5" x 3.5"