

# VIDIX CONTROL

Access Control for Every Facility



## AXX-19XX

## TOUCHLESS TECHNOLOGY READER

iClass®

### STANDARD FEATURES

- Mullion mount and single gang box mounting solutions.
- Readers include Open Supervised Device Protocol (OSDP), a new Security Industry Association (SIA) standard that together with Secure Channel Protocol (SCP) provides secure communications and central management.
- Multi-Layered Security ensures data authenticity and privacy.
- EAL5+ Certified Secure Element Hardware provides tamper-proof protection of keys/cryptographic operations.
- Near field Communications (NFC) Card Emulation—enables migration to access control on mobile devices.
- Intelligent Power Management (IPM) reduces reader power consumption by as much as 75% compared to standard operating mode.

# Technical Specifications

**AXX-I9XX**

<b>MODEL NAME</b>	i900	i910	i920	i921K
<b>COLOR</b>	Black			
<b>TRANSMIT FREQUENCY</b>	13.56 MHz			
<b>MOUNTING</b>	Mini-Mullion Size	Mullion Size	Wall Switch Size	Wall Switch Size
<b>DIMENSIONS (WxHxD)</b>	-3.3" x 4.8" x 1.0" (8.4 x 12.2 x 2.4 cm)	1.9" x 6.0" x 0.9" (4.8 cm x 15.3 cm x 2.3 cm)	3.3" x 4.8" x 1.0" (8.4 cm x 12.2 cm x 2.4 cm)	3.3" x 4.8" x 1.1" (8.5 cm x 12.2 cm x 2.8 cm)
<b>POWER SUPPLY</b>	55-16 VDC; Linear power supplies recommended			
<b>POWER SUPPLY REQUIREMENTS</b>	70mA @ 16V	110mA @ 16V	80mA @ 16V	105mA @ 16V
<b>OPERATING TEMP</b>	-31o to 150o F (-35o to 65o C)			
<b>CABLE DISTANCE</b>	500ft (150m) (22AWG) - use shielded cable for best results			
<b>ENVIRONMENTAL</b>	IP55			
<b>HOUSING MATERIAL</b>	UL94 Polycarbonate			
<b>WEIGHT</b>	7.7 oz (220g)	5.3 oz (151g)	7.7 oz (220g)	9.0 oz (256g)